

3M™ Dynatel™
Locating and Marking System



Quickly &
Accurately

Identify Underground
Assets



A complete system for damage prevention, locating, marking and mapping vital underground assets.

A Reputation of Excellence.

When you choose a quality 3M™ Dynatel™ Locator, you get outstanding performance and reliability, along with toll-free technical phone support and a service center dedicated to excellence. Our service center provides calibration, repair, upgrades and modifications for safety, performance and reliability.

Easy to Use.

Dynatel locators require little training and are simple to use. Digital LCD readouts and push-button operation make the units easy to interpret for precise locates. A bar graph on the receiver indicates received signal and proximity to the cable, and an automatic “memory” feature stores operator setup from previous use.

Precisely locates faults.

We earned our reputation for fault locating, and we continue to advance this technology today. 3M™ Dynatel™ Cable/Fault Locators identify and measure points of cable damage where there is metallic contact to earth via a conductor or cable shield. They utilize our proven fault detection method with enhanced speed, sensitivity, and noise rejection. Our multi-antenna design provides high accuracy and performance.



Photo courtesy of Minneapolis/St. Paul Metro Transit

The full line of 3M locators and markers helps you quickly and accurately identify underground assets. From finding the exact path and estimated depth of underground utilities, to locating buried passive markers, to reading and writing information directly to the iD version markers, 3M offers the precision tools needed to manage your assets. And now, certain 3M Dynatel Locators interface with select GPS/GIS field mapping instruments. Together, these tools provide a complete locating and marking solution with the performance and reliability you trust from 3M.



The most difficult
locates
just got
easier

3M™ Dynatel™ Locators

Pipe, Cable, and Electronic Marker Locators

3M Dynatel Locators combine simple interfaces, large backlit high-resolution graphics, excellent balance and ergonomics with precision locating capabilities to help you quickly and accurately identify underground assets.

Dynatel Locators can be used to trace pipe and cable paths, locate sheath faults, provide accurate pipe, cable or Sonde depth measurements, locate buried electronic markers, read/write to 3M iD Markers and interface with GPS instruments to create accurate maps of underground facilities.

Dynatel Locators are available in a range of configurations from fully-featured pipe, cable, fault and electronic marker locators to basic cable avoidance systems.

| | Cable/Pipe | Cable/Pipe/Fault |
|--|---------------------------------|------------------------------|
| M Series Advanced locator | Model 2220M 2250M 2550 | Model 2273M 2573 |
| iD Series Advanced locator Locates all EMS markers and reads/writes to iD markers | Model 2250M-iD 2550-iD | Model 2273M-iD 2573-iD |
| GPS compatible | | |
| 2200 Series Basic locator | Model 2210 Model 2250 | Model 2273 |



3M™ Dynatel™ Pipe/Cable Locator 2500 Series

Pipe/Cable Locators 2550

Pipe/Cable and Marker Locators 2550-iD

Cable/Pipe/Fault Locators 2573

Cable/Pipe/Fault and Marker Locators 2573-iD

Designed to be fast, accurate and integrated, the 3M™ Dynatel™ 2500 Series Locators and fault finders represent an advancement in locating and fault finding technology for the field professional. Offering a broad feature set with advanced digital processing, the 2500 Series locators combine simple interfaces with precision locating capabilities. All 2500 series locators offer six active frequencies and a maximum transmitter output of 12 watts providing a solution for virtually all challenging locate applications encountered in the field.

2500 Series

- Trace view mapping: graphic display of the cable direction and position
- Five locating modes: Trace View, Directional Peak, Directional Null, Single (Special) Peak, and Induction Peak locate modes
- Six active frequencies: 577, 1k, 8k, 33k, 82k, 200k (133k for Export models)
- All frequency mode in direct connection (four frequencies simultaneously)
- Four induction frequencies: 8k, 33k, 82k, 200k (133k for Export models)
- Transmitter has a 12 Watt (maximum) power output
- Fault finding option
- Electronic marker locate/read/write and alert mode option
- GPS communication capability for GIS mapping of pipe/cable path and electronic markers



**Powerful,
accurate,
and fast.**

New to the 2500 Series

Trace View mode display helps simplify locating.

The new Trace View mode presents an innovative and intuitive user interface that graphically shows the position and direction of the utility being located, simplifying path tracing applications. The unique multi-antenna array of the 2500 Series locators provides the highest level of accuracy, even in congested locates.



3M™ Dynatel™ Cable/Pipe Locators 2250M/2273M Series

Cable/Pipe Locators 2250M

Cable/Pipe and Marker Locators 2250M-iD

Cable/Pipe/Fault Locators 2273M

Cable/Pipe/Fault and Marker Locators 2273M-iD

For cable/pipe locating, the Dynatel M series has a highly accurate multi-antenna design for various user-selected locating modes—Directional Peak, Multi-Directional Null, Induction Peak, plus an ultra-sensitive Special Peak mode for extreme depths. They come equipped with several built-in features that allow accurate cable and pipe locating:

- Locate cable and pipe path
- Measure cable/pipe or Sonde depth
- Measure signal current in the cable or pipe
- Identify cable and cable pairs
- Tone shorts and grounds in aerial cable
- Locate energized power cable

The receiver includes a unique “expander” function that makes peaks and nulls more pronounced for fast tracking and pinpointing of position.

The unique Directional Peak mode combines the response from four peak antennas to indicate left/center/right direction to the cable/pipe while the bar graph and numeric display indicate the sharp and accurate dual-peak response.

Semi-automatic gain set with manual fine tuning provides maximum flexibility and control.

The Multi-Directional Null mode shows null signal response with automatic gain and utilizes the multiple antenna design to show cable/pipe location and direction on a unique compass-like graphic user interface on the high-resolution display.

For fault locating, the Dynatel locator 2273M performs all the functions of the 2250M plus the ability to find underground faults.



**Peak antenna
directional
guidance delivers
pinpoint accuracy.**

2250M/2273M Series

- Four locating modes: Directional Peak, Directional Null, Single (Special) Peak, Induction Peak, locate
- Four active frequencies, 577, 8k, 33k, 200k (133k for Export models)
- All frequency mode in direct connection (four frequencies simultaneously)
- Three induction frequencies available: 8k, 33k, 200k
- Tone mode 577Hz and 200kHz pulsed at 8Hz
- Transmitter has 3, 5, and 12 Watt (maximum) power output options
- Fault finding option
- Electronic marker locate/read/write and alert mode option.
- GPS communication capability for GIS mapping of pipe/cable path and electronic markers



3M™ Dynatel™ Advanced Pipe/Cable Locator 2220M

A new addition to the 3M Dynatel Locators 2200M series, the 2220M locator is designed to provide a simple and accurate solution to locate buried pipes, cables, and Sondes in even the most challenging field conditions. The rugged, highly sensitive receiver uses two active trace frequencies and provides a bar graph, signal strength and direction indication to the pipe/cable. In addition, the receiver is designed to detect passive power and auxiliary frequencies that do not require the use of a transmitter.

2200M

- Single and Dual Peak modes with direction. Verifies cable location and indicates direction to pipe
- Two active frequencies (8k, 82k)
- Induction mode for situations with limited or no access to the facility
- High and normal output levels for long distance locates and other varying pipe conditions
- Measures signal current in cable which helps identify target cable in congested areas
- Push-button digital depth readout of pipe or Sonde
- Transmitter has 3 and 12 Watt (maximum) power output options
- Passive Power, Passive LF, Sonde (512, 640, 33k)
- Detects cathodic protection signals

Product Feature

Two active frequencies (8k, 82k)

Dual frequency output

Passive power, Sonde locating

Single and Dual Peak modes with direction

Product Applications

Locates pipes, cables and tracer wire

Detects power signals

Locates Sondes and pipeline inspection cameras



Innovative
technology for
locating underground
utilities



1420-iD EMS Locators

- Detects industry standard electronic markers frequencies
- 3M iD marker read and write capability
- Marker maximum read range up to 8 ft. (2.4m) depth²
- GPS communication capability for GIS mapping of pipe/cable path and electronic markers¹
- Electronic marker depth estimation for 3M-iD markers
- Light weight with excellent balance and ergonomics
- Large backlit, high-resolution graphic display



| Locator features by model | 2500 Series | 2250M/2273M Series | 2220M | 1420-iD |
|-------------------------------------|-------------|--------------------|-------|---------|
| Pipe and cable locate | ● | ● | ● | |
| Electronic marker locate/read/write | ◎ | ◎ | | ● |
| GPS compatible | ● | ● | | ● |
| Active frequencies | 6 | 4 | 2 | |
| Passive power | ● | ● | ● | |
| Passive LF | ● | ● | ● | |
| Sonde locating | ● | ● | ● | ● |
| Fault locate (A-frame) | ◎ | ◎ | | |
| Transmitter (standard) | 12W | 3W | 3W | |
| Transmitter (optional) | 12W | 5W, 12W | 12W | |
| Dynacoupler size | 3" or 4.5" | 3" | 3" | |
| Ground rod and pouch | ● | ● | ● | |
| Carry bag | ● | ◎ | ● | ◎ |
| Manual | ● | ● | ● | ● |
| USB to Serial Adapter Cable | ● | ● | ● | ● |
| 2200RB rechargeable battery | ◎ | ◎ | ◎ | |
| Cigarette lighter adapter cable | ● | ◎ | ◎ | |

¹Interfaces in real time with certain models of GPS. ²Read range when reading 3M Full Range marker

● Standard feature. ◎ Optional feature.



3M™ Dynatel™ Locators

2200 Series

Cable/Pipe Locator 2250

Cable/Pipe/Fault Locator 2273

The 2200 series locator is built specifically to find the path and estimated depth of buried cables and pipes. 2200 series locators have four active frequencies: passive frequencies for power, cathodic protection, CATV and auxiliary frequencies for long distance locating from remote transmitters. They also offer toning of aerial cable, direct readout of active duct probe, and cable/pair identification.

Receivers incorporate an “expander” function to make peaks and nulls more pronounced by enhancing the amplitude difference between two conductors carrying the same tone. Both the receiver and the transmitter feature a self-test routine that is executed each time the unit is turned on.

As with other locator models, the Dynatel locator 2273 performs all the functions of the 2250 locator plus the ability to find underground faults.



3M™ Dynatel™ Locating and Marking Systems

| Receiver | 2250 | 2273 |
|---|-------------|-------------|
| Peak mode | X | X |
| Null mode | X | X |
| Differential mode | X | X |
| Push button digital depth readout | X | X |
| Cable identification | X | X |
| Measures signal current in cable | X | X |
| Direct readout of active duct probe (sonde) depth | X | X |
| Visual and audible cable locates | X | X |
| Digital fault strength indicator | | X |
| Graphic display | X | X |
| Ground level antenna | X | X |
| Expander amplifier | X | X |
| 50/60 Hz power cable locate mode | X | X |
| Transmitter | 2250 | 2273 |
| Four operator-selectable frequencies | X | X |
| Simultaneous signals | X | X |
| Built-in ohmmeter | X | X |
| Indicates presence of foreign and hazardous voltage | X | X |
| Built-in continuity test | X | X |
| Three tone application methods (direct connect, coupler, inductive) | X | X |
| Auto load impedance matching | X | X |
| High and normal output level | X | X |
| Sheath (earth return) fault-finding capability | | X |
| Fault-locate and cable-locate tones applied simultaneously | | X |



Marker Solutions for the Gas, Power, Water/Wastewater, and Communications Industry

The 3M™ Electronic Marker System helps eliminate guesswork. 3M markers operate even in the presence of metal conduit or pipe, metallic conductors, fences, AC power lines and electronic markers of other utilities. All EMS markers are color-coded to APWA standards for visual reference and each utility has its own frequency. For example, telephone utility markers are all orange in color. EMS signals provide positive identification of each utility, thus helping to reduce the risk of accidentally locating and excavating other buried facilities.



Markers that Last

With our Full-Range, Mid-Range, Ball and Near-Surface Markers, there is a marker to meet almost every need. Markers are passive antennas with no internal power source to run down. Their water-resistant, polyethylene shells are impervious to minerals, chemicals and the temperature extremes normally found underground. A four-inch Disk marker is also available for marking handholes. These markers easily attach to non-metallic lids or covers over flush-mounted facilities.

3M™ iD Markers

3M iD markers are designed to not only provide an accurate, convenient, long-lasting method of marking underground assets, but also iD markers may be programmed to include customer-specific information such as facility data, type of application, material type and size, placement date and other important details.

3M™ Ball Marker.

Engineered for narrow trench applications up to 5' in depth, the 4"-diameter ball marker has a unique self-leveling feature that helps ensure an accurate, horizontal position regardless of how it is placed in the ground. The ball contains a mixture of water and propylene glycol (a common additive in toothpaste, hair gels etc. and generally recognized as safe for use in foods by USFDA). The mixture is readily biodegradable in the environment and will not harm humans, wildlife or the environment in this application.



3M™ Near-Surface Marker.

The near-surface marker is ideal for marking underground and street-access facilities up to 2' for Passive (Non-iD marker) and 3' for iD marker in depth. Its 3.5" long cylindrical size and shape allows for easy installation in asphalt, concrete or rock without extensive digging or drilling.



3M™ Mini-Marker.

Designed for marking applications at depths up to 6', marker spokes in the 8.25" diameter mini-marker help stabilize it in the correct position after placement.



3M™ Full-Range Marker.

The full-range marker is suited for deep applications up to 8'. Its 15"-diameter makes it ideal for use as a digging shield over sensitive underground facilities.



The Smart Choice

A feature exclusive to the Dynatel EMS locator is the ability to read, write and lock programmed information into 3M™ Electronic iD Marker System. 3M iD Locators are able to pinpoint the depth and location of existing models of properly installed underground passive EMS markers — easily differentiating between standard frequencies. Detailed information can be read, stored with date/time stamp and transmitted back to your PC for enhanced resource management through a standard RS232 serial port or USB port. As referenced in a previous section, the iD Locators are now compatible with selected GPS/GIS instruments to greatly simplify the mapping process.



Please go to www.3M.com/Dynatel for more details.





3M™ Electronic Marker System Specifications

| | Telephone | Power | CATV | General | Water | Wastewater Purpose | Gas | Read Range* |
|--------------------------------------|------------|------------|--------------|------------|------------|--------------------|------------|--------------|
| Color | orange | red | black/orange | purple | blue | green | yellow | n/a |
| iD EMS iD Ball Marker Product Number | 1421-XR/iD | 1422-XR/iD | 1427-XR/iD | 1428-XR/iD | 1423-XR/iD | 1424-XR/iD | 1425-XR/iD | 5 ft. (1.5m) |
| EMS iD Near-Surface Product Number | 1432-XR/iD | 1433-XR/iD | 1437-XR/iD | 1438-XR/iD | 1434-XR/iD | 1435-XR/iD | 1436-XR/iD | 2 ft. (0.6m) |
| EMS iD Full-Range Product Number | 1250-XR/iD | 1251-XR/iD | N/A | 1248-XR/iD | 1252-XR/iD | 1253-XR/iD | 1254-XR/iD | 8 ft. (2.4m) |
| Non-iD Ball Marker XR Product Number | 1401-XR | 1402-XR | 1407-XR | 1408-XR | 1403-XR | 1404-XR | 1405-XR | 5 ft. (1.5m) |
| Near-Surface Marker Product Number | 1432 | 1433 | N/A | N/A | 1434 | 1435 | 1436 | 2 ft. (0.6m) |
| Mini-Marker Product Number | 1255 | 1256 | N/A | N/A | 1257 | 1258 | 1259 | 6 ft. (1.8m) |
| Full-Range Product Number | 1250 | 1251 | N/A | N/A | 1252 | 1253 | 1254 | 8 ft. (2.4m) |

*Read range specifies maximum distance from locator probe using 3M™ Dynatel™ Locator 1420-iD. Read range may vary on export models—refer to product bulletins.

3M™ Dynatel™ Accessories

| Image | Product | Description |
|---|---|--|
|  | 3M™ 6" (15.2 cm) Dyna-Coupler with pouch, 1196/C | Permits coupling of RF trace tone to large diameter cables, bundle cables, and cables enclosed in accessible non-metallic ducts. For use on cables and conduits with a maximum diameter of 6.9" (17.5 cm). |
|  | 3M™ Small Clip 1/4" (6.4 mm) Direct Connect, 5-foot Transmitter Cable, Telephone 9012 | Two lead, 5' (1.5 m) cables used for direct connection to conductor and ground. The 9012 cable has smaller Telco style alligator clips with an insulation piercing needle incorporated. |
|  | 3M™ Small Clip 1/4" (6.4 mm) Direct-Connect Transmitter Cable For All Cable/Fault Locators 2892 | Two lead, 10' (3 m) cable used for direct connection to cable and ground. |
|  | 3M™ Large Clip 5/8" (15.9 mm) Direct-Connect Transmitter Cable For Most Cable/Fault Locators 2876 | Two lead, 10' (3 m) cable used for direct connection to cable and ground. |
|  | 3M™ Ground Extension Cable 9043 | Extends ground capability to 12' (3.7 m). |
|  | 3M™ Earth Contact Frame 3014 | Used only when locating sheath (earth return) faults. It indicates direction to the fault and is color coded to correspond with the Receiver's indicator. |
|  | 3M™ Earth Contact Frame Cable 9026 | For use with the 3014 Earth Contact Frame for sheath (earth return) fault location; 4' (1.2 m) in length. |
|  | 3M™ Ground Rod 8006 | For applying ground capability. Stainless steel. |

| Image | Product | Description |
|---|--|--|
|  | 3M™ 3" (7.6 cm) Dyna-Coupler, 3001 | Permits coupling of RF trace tone to cables with a maximum diameter of 3" (7.6 cm). |
|  | 3M™ 4.5" (11.4 cm) Dyna-Coupler, 4001 | Permits coupling of RF trace tone to cables with a maximum diameter of 4.5" (11.4 cm). |
|  | 3M™ Coupler Cable 9011 | For use with any Dynatel Transmitter, Receiver, or Coupler: 12' (3.7 m) in length. |
|  | 3M™ Dynatel™ Locator Coupler Accessory Kit 4519 | The 4519 Accessory Kit contains a 4001 4.5" (11.4 cm) Dyna-coupler and a 9011 Coupler Cable with a case that can be attached to the transmitter. |
|  | 3M™ 3" (7.6 cm) Cable Locator Coupler Accessory Kit 3019 | The 3019 Accessory Kit contains a 3001 3" (7.6 cm) Dyna-coupler and a 9011 Coupler Cable with a case that can be attached to the transmitter. |
|  | 3M™ Soft Carrying Bag 2200 | Soft carrying bag for the 2200 series product line (2210, 2250, 2273) |
|  | 3M™ Soft Carrying Bag 2200M | Soft carrying bag for the 2200M and 2500 series product locators. |

3M™ Dynatel™ US Version Locator Kits*

Ordering Information

| | | | Cable/Pipe Locate | Fault Locate | Electronic Marker Locate | Transmitter Output | Direct Connect Cable - small clips | Direct Connect Cable - large clips | Coupler Size | 2200RB Rechargeable Battery | Cigarette Lighter Adapter Cable | Carrying Bag |
|--------------------------|--------------------------|--------------------|--------------------|--------------|--------------------------|--------------------|------------------------------------|------------------------------------|--------------|-----------------------------|---------------------------------|--------------|
| | | EMS enabled | | | | | | | | | | |
| | | Not EMS enabled | | | | | | | | | | |
| 2573 Series Kits | 80-6113-3462-6 | 2573-ID/C12 | x | x | x | 12W | x | | 3" | | x | |
| | 80-6113-3464-2 | 2573-ID/U12 | x | x | x | 12W | | x | 4.5" | x | x | x |
| | 80-6113-3458-4 | 2573-C12 | x | x | | 12W | x | | 3" | | x | |
| | 80-6113-3460-0 | 2573-U12 | x | x | | 12W | | x | 4.5" | x | x | x |
| 2550 Series Kits | 80-6113-3452-7 | 2550-ID/U12 | x | | x | 12W | | x | 4.5" | x | x | x |
| | 80-6113-3450-1 | 2550-U12 | x | | | 12W | | x | 4.5" | x | x | x |
| 2273M Series Kits | 80-6113-3044-2 | 2273M-ID/UCU12W-RT | x | x | x | 12W | x | x | 3" | x | x | x |
| | 80-6111-4091-6 | 2273M-ID/UU5W-RT | x | x | x | 5W | | x | 3" | | x | |
| | 80-6111-4095-7 | 2273M-ID/UU3W-RT | x | x | x | 3W | | x | 3" | | | |
| | 80-6111-4090-8 | 2273M-ID/UC5W-RT | x | x | x | 5W | x | | 3" | | x | |
| | 80-6111-4094-0 | 2273M-ID/UC3W-RT | x | x | x | 3W | x | | 3" | | | |
| | 80-6113-2342-1 | 2273M-ID/CATV | x | x | x | 3W | x | | 3" | | | |
| | 80-6113-3046-7 | 2273M-UCU12W/RT | x | x | | 12W | x | x | 3" | x | x | x |
| | 80-6111-4132-8 | 2273M-UU5W-RT | x | x | | 5W | | x | 3" | | x | |
| | 80-6111-4136-9 | 2273M-UU3W-RT | x | x | | 3W | | x | 3" | | | |
| | 80-6111-4131-0 | 2273M-UC5W-RT | x | x | | 5W | x | | 3" | | x | |
| | 80-6111-4135-1 | 2273M-UC3W-RT | x | x | | 3W | x | | 3" | | | |
| | 2250M Series Kits | 80-6113-3039-2 | 2250M-ID/UCU12W-RT | x | | x | 12W | x | x | 3" | x | x |
| 80-6111-4140-1 | | 2250M-ID/UU5W-RT | x | | x | 5W | | x | 3" | | x | |
| 80-6111-4144-3 | | 2250M-ID/UU3W-RT | x | | x | 3W | | x | 3" | | | |
| 80-6111-4139-3 | | 2250M-ID/UC5W-RT | x | | x | 5W | x | | 3" | | x | |
| 80-6111-4143-5 | | 2250M-ID/UC3W-RT | x | | x | 3W | x | | 3" | | | |
| 80-6113-3041-8 | | 2250M-UCU12W/RT | x | | | 12W | x | x | 3" | x | x | x |
| 80-6111-4148-4 | | 2250M-UU5W-RT | x | | | 5W | | x | 3" | | x | |
| 80-6111-4152-6 | | 2250M-UU3W-RT | x | | | 3W | | x | 3" | | | |
| 80-6111-4147-6 | | 2250M-UC5W-RT | x | | | 5W | x | | 3" | | x | |
| 80-6111-4151-8 | | 2250M-UC3W-RT | x | | | 3W | x | | 3" | | | |
| 2220M Series Kits | 80-6113-3107-7 | 2220M-CU12W/RT | x | | | 12W | x | x | 3" | x | x | x |
| | 80-6113-2585-5 | 2220M-U3W | x | | | 3W | | x | | | | x |
| | 80-6113-2681-2 | 2220M-U3W3-CPLR | x | | | 3W | | x | 3" | | | x |
| | 80-6113-2586-3 | 2220M-C3W-CPLR | x | | | 3W | x | | 3" | | | x |
| 2273 Series Kits | 80-6109-9352-1 | 2273-U5P3/A | x | x | | 5W | x | | 3" | | x | |
| | 80-6109-9353-9 | 2273-U5T3/A | x | x | | 5W | x | | 3" | | x | |
| | 80-6108-4745-3 | 2273-U3P3 | x | x | | 3W | | x | 3" | | | |
| | 80-6108-4739-6 | 2273-U3T3 | x | x | | 3W | x | | 3" | | | |
| 2250 Series Kits | 80-6108-4727-1 | 2250-U3P3 | x | | | 3W | | x | 3" | | | |
| | 80-6108-4721-4 | 2250-U3T3 | x | | | 3W | x | | 3" | | | x |
| 1420 | 80-6111-4087-4 | 1420 | | | x | | | | | | | |

**3M™ Dynatel™ Export Version Locator Kits*
Ordering Information**

| | | | Cable/Pipe Locate | Fault Locate | Electronic Marker Locate | Transmitter Output | Direct Connect Cable - small clips | Direct Connect Cable - large clips | Coupler Size | 2200RB Rechargeable Battery | Cigarette Lighter Adapter Cable | Carrying Bag |
|----------------------------|----------------|--------------------|-------------------|--------------|--------------------------|--------------------|------------------------------------|------------------------------------|--------------|-----------------------------|---------------------------------|--------------|
| | | | EMS enabled | | | | | | | | | |
| | | | Not EMS enabled | | | | | | | | | |
| 2573-E Series Kits | 80-6113-3470-9 | 2573E-ID/CU12 | x | x | x | 12W | x | x | 4.5" | x | x | x |
| | 80-6113-3468-3 | 2573E-CU12 | x | x | | 12W | x | x | 3" | x | x | x |
| 2550-E Series Kits | 80-6113-3466-7 | 2550E-ID/CU12 | x | | x | 12W | x | x | 4.5" | x | x | x |
| | 80-6113-3465-9 | 2550E-CU12 | x | | | 12W | x | x | 4.5" | x | x | x |
| 2273M-E Series Kits | 80-6113-3043-4 | 2273M-ID/ECU12W-RT | x | x | x | 12W | x | x | 3" | x | x | x |
| | 80-6111-4093-2 | 2273M-ID/EU5W-RT | x | x | x | 5W | | x | 3" | | x | |
| | 80-6111-4092-4 | 2273M-ID/EC5W-RT | x | x | x | 5W | x | | 3" | | x | |
| | 80-6113-3042-6 | 2273M-ECU12W/RT | x | x | | 12W | x | x | 3" | x | x | x |
| | 80-6111-4134-4 | 2273M-EU5W/RT | x | x | | 5W | | x | 3" | | x | |
| | 80-6111-4133-6 | 2273M-EC5W/RT | x | x | | 5W | x | | 3" | | x | |
| 2250M-E Series Kits | 80-6113-3038-4 | 2250M-ID/ECU12W-RT | x | | x | 12W | x | x | 3" | x | x | x |
| | 80-6111-4142-7 | 2250M-ID/EU5W-RT | x | | x | 5W | | x | 3" | | x | x |
| | 80-6111-4141-9 | 2250M-ID/EC5W-RT | x | | x | 5W | x | | 3" | | x | x |
| | 80-6113-3037-6 | 2250M-ECU12W/RT | x | | | 12W | x | x | 3" | x | x | x |
| | 80-6111-4150-0 | 2250M-EU5W/RT | x | | | 5W | | x | 3" | | x | x |
| | 80-6111-4149-2 | 2250M-EC5W/RT | x | | | 5W | x | | 3" | | x | x |
| 2220M Series Kits | 80-6113-3107-7 | 2220M-CU12W/RT | x | | | 12W | x | x | 3" | x | x | x |
| | 80-6113-2585-5 | 2220M-U3W | x | | | 3W | | x | | | | x |
| | 80-6113-2681-2 | 2220M-U3W3-CPLR | x | | | 3W | | x | 3" | | | x |
| | 80-6113-2586-3 | 2220M-C3W-CPLR | x | | | 3W | x | | 3" | | | x |
| 2273-E Series Kits | 80-6109-9337-2 | 2273-E5T3 | x | x | | 5W | x | 3" | | x | | |
| 2250-E Series Kits | 80-6109-9335-6 | 2250-E5T3 | x | | | 5W | x | 3" | | x | | |
| 1420E | 80-6111-4646-7 | 1420E | | | x | | | | | | | |

All 3M™ Dynatel™ Cable/Pipe Locator Kits include locator receiver, transmitter, ground rod, manual, direct connect and accessory cables.

3M and Dynatel are trademarks of 3M Company.

Conditional Limited Warranty

3M provides the following Conditional Limited Warranty for its iD Electronic Marker Products: When installed in accordance with 3M's installation instructions, 3M warrants iD Electronic Markers for a period of ten (10) years from the date of purchase of the product, to be free from defects in material and manufacture, provided iD Electronic Markers are located with 3M™ Dynatel™ Locators or other brand locators as may be designated by 3M in writing. This warranty does not extend to iD Electronic Markers that have been subjected to misuse or improper application or that have been repaired or altered by others. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OF FITNESS FOR A PARTICULAR PURPOSE.** If the iD Marker is found to be defective within the warranty period, your exclusive remedy shall be, at 3M's options, to repair or replace the iD Markers or refund the purchase price. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

Conditional Lifetime Warranty

3M provides the following Conditional Limited Warranty for its Electronic Marker Products (non-iD versions only): When installed in accordance with 3M's installation instructions, 3M warrants Electronic Markers for the lifetime of the product, to be free from defects in material and manufacture, provided the Electronic Markers are located with 3M™ Dynatel™ Locators or other brand locators as may be designated by 3M in writing. This warranty does not extend to Electronic Markers that have been subjected to misuse or improper application or that have been repaired or altered by others. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OF FITNESS FOR A PARTICULAR PURPOSE.** If the Electronic Marker is found to be defective during the normal lifetime of the product, your exclusive remedy shall be, at 3M's options, to repair or replace the Electronic Markers or refund the purchase price. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

Limited Product Warranty

All 3M products, locating instruments (except accessories), manufacture dated test leads, and rechargeable batteries will conform to 3M's published specifications and will be free from defects in material and manufacture for a period of twelve (12) months from the date of purchase. Dry cell batteries included in any of 3M's products are warranted only to the extent the battery manufacturer determines such batteries are covered by its warranty. Accessories for locating instruments are warranted for ninety (90) days after purchase. 3M's obligations and liability under this warranty are limited to repairing, replacing or refund of the purchase price, at 3M's option, any of 3M's products which, after normal and proper usage, are determined by 3M to be defective. This warranty does not extend to any of 3M's products which have been subjected to misuse, neglect, accident or improper applications, nor shall it extend to products which have been repaired or substantially altered outside 3M's manufacturing or repair facility, nor to any associated instruments, equipment or apparatus. Before utilizing any of 3M's products, BUYER should determine the suitability of the product for BUYER'S intended use. **3M MAKES NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** In no case shall 3M be liable for any special, incidental, or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability or any other legal theory. This limitation does not apply to claims for personal injury.



3M Track and Trace Solutions

6801 River Place Blvd.
Austin, TX 78726-9000
800/426 8688
Fax 800/626 0329
www.3M.com/Dynatel

Please recycle. Printed in USA.
© 3M 2010. All rights reserved.
78-9000-0329-0 Rev A