
Protect Downstream Equipment Distribut Linc Ene

Distributed by: Linc Energy Systems www.LincEnergySystems.com

BASKET STRAINER





HIGHLIGHTS

- Protect downstream equipment from dangerous debris such as loose scale, weld beads, grit, metal shavings, PTFE and other damaging foreign material
- Inexpensive protection for meters, regulators, valves, pumps and other mechanical equipment
- · Highly effective and reusable
- Manufactured in USA

SPECIFICATIONS

- Stainless Steel (standard)/Carbon Steel (optional)
- 1/8" diameter holes on 3/16" centers
- Mesh lining available (20 Mesh through 120 Mesh) on inside or outside
- From ³/₄" NPS to greater than 36" NPS
- Positive identification stamped on handle
- ANSI 150, 300, 600, 900 and 1500
- Handles are 1" wide x 3" long
- 150% Open Area Standard, 100% to 300% available
- · Custom sizes and specifications are available

NOMINAL PIPE SIZE	DIAMETER, OD (INCHES)			воттом	PLATE	BASKET HEIGHT (INCHES)			
	ANSI 150	ANSI 300	ANSI 600	DIAMETER (INCHES)	THICKNESS GAUGE	100% OPEN	150% OPEN	200% OPEN	300% OPEN
3/4"	2.13	2.5	2.5	0.38	11	1.5	2	3	4
1"	2.5	2.75	2.75	0.5	11	1.5	2	3	4
11/2"	3.25	3.63	3.63	0.075	11	2	2.5	3.5	5
2"	4	4.25	4.25	1	11	2.5	3	4	6
21/2"	4.75	5	5	1.25	11	2.5	3	4.5	6
3"	5.25	5.75	5.75	1.5	11	3	4.5	6	8
4"	6.75	7	7.5	2	11	4	5	7	11
6"	8.63	9.75	10.38	3	11	5.5	8	11	17
8"	10.88	12	12.5	4	-11	7	11	14	21
10"	13.25	14.13	15.63	5	11	8	13	17	26
12"	16	16.5	17.88	6	11	10	15	20	31
14"	17.38	19	19	7	11	10	16	22	33
16"	20.13	21.13	21.88	8	11	12	19	24	37
18"	21.25	23.38	23.75	9	11	14	21	27	41
20"	23.5	25.63	26.63	10	11	16	24	31	48
24"	27.88	30.38	30.88	12	11	18	28	37	57
30"	30.5	32.875	34.13	13	11	22	34	46	71
36"	41.25	44	44.5	17.5	11	27	42	58	85



International Measurement and Control Systems

Larger sizes are available, please contact IMAC.

Dimensions are for reference only, please consult factory if dimension is critical or drawing is required.